Selectarc 54

Rutile Electrode Nice appearence



Montano

Allt inom stål & smide www.montano.se

Classification

AWS A5.1 E6013 EN 499 E 42 0 RR 1 2

ISO 2560-A E 42 0 RR 1 2

Description & Applications

Heavy coated rutile electrode for general use. Especially recommended for downhand weldinf, for tillet welds and vertical up position. Soft arc, few spatters, self lifting slag, excellent bead appearance.

Main applications: Currently used for welding mechanical constructions, shipbuilding, blacksmithing, boiler making...

Construction steels for general use, tube steels, ship steels					
EN- Designation	S185 - S355	L210 - L360	P235 - P355		
Ship steels	Quality A & B				
ASTM	A285 grade C	A414 grade C, D, E, F	A442 grade 55, 60	A515 grade 55, 60	
Typical Wld metal Composition (%)					
С	Si	Mn	P	S	Fe
<0,10	0,4	0,6	<0,025	<0,025	Rem.
All Weld Metal Mechanical Properties					
R _e (MPa)	R _m (MPa)	A ₅ (%)	KV (J)	KV (J)	KV (J)
>400	510-580	>22	+ 20°C >64	+/- 0°C >47	- 20°C >28
Welding Current & Instructions					
Dim. Ø	2,0	2,5	3,2	4,0	5,0
(A)	55	70	115	150	180



= - ~ 45V